



Technical information EasyReach® Tool

What should be done and what should not be done ...

for the biodecontamination of insulators and RABSS

Yes it should be done:

Clean before disinfecting even when using a gaseous decontamination process.

Clean from the cleanest to the dirtiest, usually top to bottom and back to front.

Clean in a straight line, each new pass overlap 10 to 25%.

It should not be done:

Allow a disinfectant to remain in contact with surfaces for longer than recommended by the manufacturer.

Allow the liquid to reach areas that can not be reached to dry, as it corrodes the equipment especially where it can not evaporate. Apply to a wipe first or use presaturated wipes.

Leave areas of paint or coatings unrepaired if scratched or damaged, as they are usually mildly coated steel that corrodes if the liquid gets underneath the coating.

Smart quality by DTB

Features and Benefits

Pads that fits well in 100% polyester base

- Safe in use, allowing efficient disinfection and disposal.
- Very low particulate emission for Class A environments.

Dry or presaturated pads to choose.

- It can be used with a detergent or disinfectant of your choice using existing validation.
- Presaturated pads eliminate the need for spray bottles in the controlled environment.

Short handle only 40cm.

- Small enough to pass in the narrowest parts of transfer ports

Profile under pivoting head

- It ensures that even the most difficult areas can be reached with minimum effort, maintaining good contact with the surface.

Lightweight stainless steel frame and handle

- Suitable for single-handed use, reducing fatigue and encouraging best compliance practices.
- Suitable for autoclaving at 121 ° C and compatible with a wide range of cleaning and disinfecting products, including vaporized hydrogen peroxide.

Rounded edges

- They assure that there is no possibility of damage or scratching of the equipment.

Fixed length or telescopic handles

- It extends up to 72 cm to facilitate cleaning in large, custom RABS or incubators, minimizing the risk of stress by overtraining.
- Reduces the likelihood of containment devices being contaminated, while operators are cleaning

Hook to hang

- Allows storage away from work surfaces.